

Multi-Mile[®]

MAXIMUM MILEAGE SECURITY AND COMFORT



**PASSENGER, PERFORMANCE &
LT/RV TIRES CATALOG 2009**

TABLE OF CONTENTS

PASSENGER

ULTRA HIGH PERFORMANCE (V & W Rated)	
SCEPTOR G/P 326R	1
HIGH PERFORMANCE (H, V & W Rated)	
MIRADA SPORT GTX.....	2 - 3
VALUE LINE PERFORMANCE (T & H Rated)	
SOLAR HP430	4
OWL & SBL PERFORMANCE (S & T Rated)	
GRAND AM RADIAL G/Ts.....	5
GRAND SPIRIT G/T RADIAL.....	6
LUXURY TOURING (T, H & V Rated)	
GRAND TOUR SLi.....	7-8
TOURING ALL SEASON	
ULTREX AS4 TOURING.....	9
PASSENGER ALL SEASON	
MATRIX	10
VALUE ALL SEASON	
EPIC TOUR / CLASSIC ALL SEASON	11
CUSTOM 428+.....	12

SUV/LIGHT TRUCK

SPORT LIGHT TRUCK	
HTR SPORT H/P	13
TOURING CUV/SUV	
MIRADA CROSSTOUR SLX	14
PREMIUM ALL SEASON SUV/LT	
WILD COUNTRY SPORT H/T.....	15
PREMIUM ALL TERRAIN SUV/LT	
WILD COUNTRY RADIAL XTX SPORT	16 - 17
ALL POSITION/ALL TERRAIN SUV/LT	
WILD COUNTRY RADIAL XRT II	18 - 19
VALUE ALL TERRAIN SUV/LT	
TRAIL GUIDE RADIAL A/P	20
COMMERCIAL HIGHWAY	
POWER KING LT RADIAL HIGHWAY.....	21
SOLID TRAC RADIAL A/S	22
TRIANGLE TR645	23
COMMERCIAL TRACTION	
WILD SPIRIT RADIAL TXR II	24
PREMIUM MUD TRACTION	
WILD COUNTRY RADIAL RVT	25

WINTER

PASSENGER	
ARCTIC CLAW WINTER Txi.....	26 - 27
SUV/LIGHT TRUCK	
ARCTIC CLAW WINTER Xsi	28 - 29

NEUTRAL TIRE PICTURES AND WARRANTY

TIRE PICTURES	
NEUTRAL PICTURES.....	30 - 31
WARRANTY	
W & M NATIONWIDE LIMITED WARRANTY	32

The logo features the brand name "Multi-Mile" in a bold, white, sans-serif font. The text is set against a red, stylized banner that has a wavy, ribbon-like appearance. A registered trademark symbol (®) is positioned to the upper right of the word "Mile".

Multi-Mile[®]

————— TIRES

Maximum Mileage, Security and Comfort

Multi-Mile[®] brand tires are manufactured to exacting manufacturing standards. They are second to none in the industry, including the “majors”. With Multi-Mile[®] tires, Independent Tire Dealers have the opportunity to offer superior value vs. the comparable brand name competition - and to receive margins the brand names just can't match.

Every effort has been made to verify the accuracy of the listed specifications. TBC Corporation, and TBC Private Brands cannot be held responsible for any discrepancies, and as such the information should be considered as approximate.

SCEPTOR GP326R

ULTRA HIGH PERFORMANCE - V RATED

ULTRA HIGH PERFORMANCE AT A VALUE PRICE. A V-RATED TIRE DESIGNED TO PERFORM AS WELL AS IT LOOKS.

- *Advanced Directional Tread Design Provides Superior, Acceleration, Cornering And Braking Performance*
- *Solid Center Rib Design Provides Excellent High Speed Stability And Responsiveness*
- *Large Swept Back Channels Clear Water From Tread For Superior Wet Traction*
- *Styled Black Sidewall With Performance Cosmetics*

UTQG: 360 AA A



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
SP-58	215/50R17	91V	SL	360 AA A	10	BLK	7.0	8.9	25.50	1356 @ 51	25
SP-53	215/45R17	90V	SL	360 AA A	10	BLK	7.0	8.4	24.60	1202 @ 51	23
SP-71	225/45R17	90V	SL	360 AA A	10	BLK	7.5	8.9	25.00	1323 @ 51	24
SP-54	235/45R17	93V	SL	360 AA A	10	BLK	8.0	9.3	25.40	1433 @ 51	26
SP-55	245/45R17	95V	SL	360 AA A	10	BLK	8.0	9.6	25.70	1521 @ 51	27
SP-04	205/40R17	80V	SL	360 AA A	10	BLK	7.5	8.3	23.50	992 @ 51	20
SP-78	225/40R18	88V	SL	360 AA A	10	BLK	8.0	9.1	25.10	1235 @ 51	26
SP-82	235/40R18	91V	SL	360 AA A	10	BLK	8.5	9.5	25.40	1356 @ 51	25
SP-84	245/40R18	93V	SL	360 AA A	10	BLK	8.5	9.8	25.70	1433 @ 51	26
SP-16	215/35R18	84V	SL	360 AA A	10	BLK	7.5	8.6	23.90	1102 @ 51	21
TS-42	245/35ZR20	95W	SL	360 AA A	10	BLK	8.5	9.8	26.77	1521 @ 51	27
TS-20	255/35ZR20	97W	SL	360 AA A	10	BLK	9.0	10.2	27.01	1609 @ 51	28

MIRADA SPORT GTX

HIGH PERFORMANCE ALL SEASON - H, V & W RATED

A TRUE ALL SEASON HIGH PERFORMANCE TIRE DESIGNED TO PROVIDE THE PERFECT BALANCE OF PERFORMANCE AND COMFORT. THE MIRADA SPORT GTX WAS DEVELOPED TO PROVIDE PERFORMANCE CARS, COUPES AND SEDANS WITH GREAT TREADWEAR, RESPONSIVE HANDLING AND ALL WEATHER TRACTION.

- *Wide, Deep Circumferential Grooves To Maximize Traction And Vehicle Response*
- *Computer-Optimized Tread Design And Variable-Siped Pattern For A Smooth Quiet Ride*
- *Large Shoulder Blocks For Increased Cornering And Handling*
- *High Grip Tread Compound For Superior Wet, Dry And Snow Traction*
- *Twin Continuous Center Ribs Enhance High Speed Stability*
- *W & M - Free Replacement 1st 50% Treadwear*
- *Free Consumer Roadside Assistance Warranty*

UTQG: 400 A A



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS.@ PSI	SHIP WEIGHT (lbs.)
21802	P185/65R14	85H	SL	400A A	10	BLK	5.5	7.4	23.4	1124@44	16
21808	P195/65R14	88H	SL	400A A	10	BLK	6.0	7.9	24.0	1235@44	19
21801	P185/60R14	82H	SL	400A A	10	BLK	5.5	7.4	22.8	1047@44	16
21806	P195/60R14	85H	SL	400A A	10	BLK	6.0	7.9	23.2	1135@44	18
21813	P205/60R14	88H	SL	400A A	10	BLK	6.0	8.1	23.8	1235@44	18
21817	P215/60R14	91H	SL	400A A	10	BLK	6.5	8.7	24.2	1354@44	20
21803	P185/65R15	86H	SL	400A A	10	BLK	5.5	7.4	24.4	1168@44	18
21809	P195/65R15	89H	SL	400A A	10	BLK	6.0	8.0	25.0	1279@44	20
21815	P205/65R15	92H	SL	400A A	10	BLK	6.0	8.2	25.4	1400@44	21
21819	P215/65R15	95H	SL	400A A	10	BLK	6.5	8.9	26.1	1510@44	23
21807	P195/60R15	87H	SL	400A A	10	BLK	6.0	7.8	24.2	1190@44	19
21814	P205/60R15	90H	SL	400A A	10	BLK	6.0	8.1	24.7	1301@44	21
21818	P215/60R15	93H	SL	400A A	10	BLK	6.5	8.8	25.2	1411@44	21
21823	P225/60R15	95H	SL	400A A	10	BLK	6.5	9.1	25.7	1521@44	23
21805	P195/55R15	84V	SL	400A A	9	BLK	6.0	7.8	23.4	1102@44	19
21804	P195/50R15	81V	SL	400A A	10	BLK	6.0	7.8	22.8	1019@44	20
21811	P205/50R15	84V	SL	400A A	10	BLK	6.5	8.3	23.1	1113@44	21
21820	P225/50R15	90V	SL	400A A	10	BLK	7.0	9.0	24.0	1301@44	23

MIRADA SPORT GTX

HIGH PERFORMANCE ALL SEASON - H, V & W RATED

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
21830	P205/60R16	91H	SL	400A A	10	BLK	6.0	8.3	25.6	1356@44	23
21832	P215/60R16	94H	SL	400A A	10	BLK	6.5	8.7	26.2	1477@44	24
21824	P225/60R16	97H	SL	400A A	10	BLK	6.5	9.0	26.7	1609@44	26
21825	P235/60R16	99H	SL	400A A	10	BLK	7.0	9.5	27.1	1709@44	27
21812	P205/55R16	89V	SL	400A A	10	BLK	6.5	8.4	24.9	1279@44	23
21816	P215/55R16	91V	SL	400A A	10	BLK	7.0	8.8	25.2	1356@44	23
21822	P225/55R16	94V	SL	400A A	10	BLK	7.0	9.1	25.7	1477@44	25
21821	P225/50R16	91V	SL	400A A	10	BLK	7.0	9.0	24.8	1367@44	25
21826	P245/50R16	96V	SL	400A A	11	BLK	7.5	9.8	25.7	1576@44	27
21827	P255/50R16	99V	SL	400A A	11	BLK	8.0	10.5	26.0	1687@44	29
21829	205/45R16	83V	SL	400A A	10	BLK	7.0	8.2	23.3	1074@44	22
21840	215/55R17	94V	SL	400A A	11	BLK	7.0	8.8	26.3	1477@44	26
21836	P225/55R17	95V	SL	400A A	10	BLK	7.0	9.1	26.8	1521@44	27
21844	235/55R17	99V	SL	400A A	11	BLK	7.5	9.7	27.2	1709@51	30
21835	P215/50R17	93V	SL	400A A	10	BLK	7.0	8.8	25.5	1433@50	24
21841	225/50R17	94V	SL	400A A	10	BLK	7.0	8.8	25.9	1477@44	26
21842	235/50R17	96V	SL	400A A	10	BLK	7.5	9.6	26.3	1565@51	28
21834	215/45R17	91V	SL	400A A	10	BLK	7.0	8.5	24.6	1356@50	24
21843	225/45R17	94V	RF	400A A	11	BLK	7.5	8.3	25.1	1477@50	30
21837	235/45R17	97V	SL	400A A	10	BLK	8.0	9.4	25.3	1609@50	27
21838	P245/45R17	95V	SL	400A A	11	BLK	8.0	9.7	25.7	1521@44	28
21831	205/40R17	84V	SL	400A A	10	BLK	7.5	8.5	23.5	1102@50	22
21833	215/40R17	87V	SL	400A A	10	BLK	7.5	8.7	23.9	1202@50	23
21845	225/60R18	99H	SL	400A A	11	BLK	6.5	9.0	28.7	1709@51	28
21846	245/45R18	96W	SL	400A A	11	BLK	8.0	9.8	25.6	1565@51	29
21847	225/40R18	92W	RF	400A A	11	BLK	8.0	9.2	25.0	1389@50	25
21848	245/40R18	97W	RF	400A A	11	BLK	8.5	9.7	26.6	1609@50	28

SOLAR HP430

VALUE PERFORMANCE - T, H & V RATED

PERFORMANCE AT AN AFFORDABLE PRICE. AVAILABLE IN SOME OF THE MOST POPULAR SIZES AND SPEED RATINGS. COVERING A WIDE RANGE OF VEHICLE FITMENTS.

- All Season Tread Design For Dependable Traction And Handling
- Cross Channels For Improved Wet Traction
- Stylized Black Sidewall
- T, H & V Performance Rated

UTQG: 400 A A / 440 A A



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
SHP06*	175/70R13	82T	SL	400 A A	9	BLK	5.0	7.0	22.7	1047@44	16
SHP11*	185/70R13	86T	SL	400 A A	10	BLK	5.5	7.4	23.2	1168@44	18
SHP23*	185/70R14	88T	SL	400 A A	10	BLK	5.5	7.4	24.3	1235@44	18
SHP38*	195/70R14	91T	SL	400 A A	10	BLK	6.0	7.9	24.8	1356@44	19
SHP39*	205/70R14	95T	SL	400 A A	10	BLK	6.0	8.2	25.4	1521@44	21
SHP61	175/65R14	82H	SL	440 A A	10	BLK	5.0	7.0	23.0	1047@44	17
SHP62	185/65R14	86H	SL	440 A A	10	BLK	5.5	7.4	23.5	1168@44	18
SHP40	185/60R14	82H	SL	440 A A	10	BLK	5.5	7.4	22.8	1047@44	16
SHP71	195/60R14	86H	SL	440 A A	10	BLK	6.0	7.9	23.2	1168@44	20
SHP29	205/70R15	96T	SL	440 A A	10	BLK	6.0	8.2	26.3	1565@44	23
SHP33	215/70R15	98T	SL	440 A A	10	BLK	6.5	8.7	26.9	1655@44	25
SHP35	185/65R15	88H	SL	440 A A	10	BLK	5.5	7.4	24.5	1235@44	19
SHP28	195/65R15	91H	SL	440 A A	10	BLK	6.0	7.9	25.0	1360@44	20
SHP30	205/65R15	94H	SL	440 A A	10	BLK	6.0	8.2	25.5	1480@44	23
SHP68	215/65R15	96H	SL	440 A A	10	BLK	6.5	8.7	26.0	1565@44	25
SHP73	185/60R15	84H	SL	440 A A	10	BLK	5.5	7.4	23.7	1102@44	19
SHP41	195/60R15	88H	SL	440 A A	10	BLK	6.0	7.9	24.2	1235@44	19
SHP43	205/60R15	91H	SL	440 A A	10	BLK	6.0	8.2	24.7	1360@44	23
SHP22	215/60R15	94H	SL	440 A A	10	BLK	6.5	8.7	25.2	1477@44	23
SHP19	205/60R16	92H	SL	440 A A	10	BLK	6.0	8.2	25.7	1389@44	22
SHP48	215/60R16	95H	SL	440 A A	10	BLK	6.5	8.7	26.1	1521@44	25
SHP52	225/60R16	98H	SL	440 A A	10	BLK	6.5	9.0	26.6	1655@44	26
SHP42	205/55R16	91H	SL	440 A A	10	BLK	6.5	8.4	24.9	1360@44	22
SHP57	215/55R16	93V	SL	440 A A	10	BLK	7.0	8.9	25.3	1433@44	24
SHP44	225/50R16	92V	SL	440 A A	10	BLK	7.0	9.2	24.9	1389@44	26

* Slightly Different Tread Design

GRAND AM RADIAL G/T'S

OWL PERFORMANCE - S & T RATED

AN ALL SEASON TIRE FOR THOSE WHO PREFER THE HANDLING AND COSMETIC APPEARANCE OF A PERFORMANCE TIRE TO STANDARD ALL SEASON TIRES.

- Stylized Outline White Letters
- Performance All Season Tread Design
- Flatter Tread Profile For Improved Cornering & Handling
- S & T Speed Rated

UTQG: 440 A B / 440 A C



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
39B13*	P205/60R13	86T	SL	440A B	10	OWL	6.0	7.9	22.8	1179@44	18
47B39*	P205/70R14	93T	SL	440A B	10	OWL	6.0	8.2	25.3	1433@44	21
GAM47	215/70R14	96T	SL	440A B	10	OWL	6.5	8.7	25.8	1565@44	22
GAM60	225/70R14	99T	SL	440A B	10	OWL	6.5	8.9	26.3	1709@44	23
39B38*	P215/60R14	91T	SL	440A B	10	OWL	6.5	8.4	24.2	1345@44	21
67B47*	P235/60R14	96T	SL	440A B	10	OWL	7.0	9.1	25.1	1565@44	23
GAM33	215/70R15	98T	SL	440A B	10	OWL	6.5	8.7	26.7	1653@44	23
GAM45	225/70R15	100T	SL	440A B	10	OWL	6.5	8.7	27.4	1764@44	25
GAM49	235/70R15	103T	SL	440A B	10	OWL	7.0	9.5	27.9	1929@44	27
GAM64	255/70R15	108T	SL	440A B	10	OWL	7.5	10.4	29.0	2205@44	31
GAM68	215/65R15	96T	SL	440A B	10	OWL	6.5	8.4	26.0	1565@44	22
GAM41	195/60R15	88T	SL	440A B	10	BLK	6.0	7.6	24.3	1190@44	19
GAM43	205/60R15	91T	SL	440A B	10	BLK	6.0	7.8	24.7	1301@44	20
GAM44	215/60R15	94T	SL	440A B	10	OWL	6.5	8.4	25.2	1411@44	22
GAM51	235/60R15	98T	SL	440A B	10	OWL	7.0	9.2	26.1	1642@44	25
67B51*	P245/60R15	100T	SL	440A B	10	OWL	7.0	9.5	26.6	1753@44	26
GAM52	255/60R15	102T	SL	440A B	10	OWL	7.5	9.7	27.0	1885@44	28
GAM53	275/60R15	107T	SL	440A B	10	OWL	8.0	10.7	28.1	2149@44	30
J2-46**	P265/50R15	99S	SL	440A C	10	OWL	8.5	10.5	25.6	1720@35	27
GAM74	295/50R15	108S	SL	440A C	10	OWL	9.5	11.8	26.8	2061@44	32

* Branded Grand Prix Performance G/T (See picture on page 30)

** Branded Grand Spirit Radial G/T (See picture on page 30)

GRAND SPIRIT G/T RADIAL

SBL PERFORMANCE - T RATED

AN ALL SEASON TIRE FOR THOSE WHO PREFER THE HANDLING AND COSMETIC APPEARANCE OF A PERFORMANCE TIRE TO STANDARD ALL SEASON TIRES.

- *Stylized Solid Black Letters*
- *Performance All Season Tread Design*
- *Flatter Tread Profile For Improved Cornering & Handling*
- *T Speed Rated*

UTQG: 440 A B



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS.@ PSI	SHIP WEIGHT (lbs.)
U6-33	P185/60R14	82T	SL	440A B	10	BLK	5.5	7.15	22.80	1047@44	17
U6-35	P195/60R14	85T	SL	440A B	10	BLK	6.0	7.6	23.28	1135@44	18
U6-41	P195/60R15	87T	SL	440A B	10	BLK	6.0	7.6	24.30	1190@44	19
U6-43	P205/60R15	90T	SL	440A B	10	BLK	6.0	7.83	24.73	1301@44	20
U6-46	P225/60R15	95T	SL	440A B	10	BLK	6.5	8.63	25.67	1521@44	23
U6-59	P235/55R16	96T	SL	440A B	10	BLK	7.5	9.65	26.15	1565@44	24

GRAND TOUR SLI - H & V RATED

LUXURY TOURING

A TOURING TIRE DESIGNED FOR TODAY'S LUXURY SEDANS. COMBINING THE RESPONSIVE HANDLING OF A PERFORMANCE TIRE WITH THE COMFORT OF A TOURING TIRE. THE GRAND TOUR SLI WAS ENGINEERED TO MEET THE NEEDS OF A WIDE RANGE OF TODAY'S VEHICLES.

- Advanced Rubber Compounds For Superior All Weather Performance
- Computer Designed Tread With Circumferential Grooves For Superior Traction
- "VPS" (Variable Pitch sequence) For An Exceptionally Quiet Ride
- Transverse Shoulder Grooves For Excellent Wet Traction
- Wide, Aggressive Shoulder Elements For Responsive Handling
- Spiral Wound Nylon Tread Cap For Enhanced High Speed Stability
- W & M - Free Replacement 1st 50% Treadwear

UTQG: 620 A B (T Rated)
500 A A (H Rated)
400 A A (V Rated)



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
SLG35**	195/60R14	86H	SL	500A A	11	BLK	6.0	8.0	23.2	1168@44	18
GTS28	195/65R15	91H	SL	500A A	11	BLK	6.0	8.1	25.0	1356@44	20
GTS30	205/65R15	94H	SL	500A A	11	BLK	6.0	8.3	25.4	1477@44	22
GTS41	195/60R15	88H	SL	500A A	11	BLK	6.0	8.0	24.2	1235@44	20
GTS43	205/60R15	91H	SL	500A A	11	BLK	6.0	8.3	24.7	1356@44	21
SLG27**	195/55R15	85V	SL	400A A	11	BLK	6.0	7.9	23.4	1135@44	20
GTS61	205/60R16	92H	SL	500A A	11	BLK	6.0	8.4	25.7	1389@44	22
SLG48**	215/60R16	95V	SL	400A A	11	BLK	6.5	9.0	26.1	1521@44	25
GTS46	225/60R16	98H	SL	620A B	11	BLK	6.5	9.1	26.6	1653@44	25
GTS56	235/60R16	100H	SL	500A A	11	BLK	7.0	9.5	27.1	1764@44	27
GTS42	205/55R16	91H	SL	500A A	11	BLK	6.5	8.6	24.9	1356@44	22
SLG57**	215/55R16	93H	SL	500A A	11	BLK	7.0	8.9	25.3	1433@44	23
SLG42**	225/55R16	95V	SL	400A A	11	BLK	7.0	9.4	25.8	1521@44	25
GTS51	225/50R16	92V	SL	400A A	11	BLK	7.0	9.2	24.9	1389@44	24
GTS71	215/55R17	94V	SL	400A A	11	BLK	7.0	8.9	26.3	1477@44	26
GTS88	225/55R17	97V	SL	400A A	11	BLK	7.0	9.3	26.8	1609@44	27
GTS89	235/55R17	99H	SL	500A A	11	BLK	7.5	9.8	27.2	1709@44	28
GTS58	215/50R17	91V	SL	400A A	11	BLK	7.0	8.9	25.5	1356@44	25
GTS66	225/50R17	94V	SL	400A A	11	BLK	7.0	9.7	25.9	1477@44	26
GTS69	235/50R17	96V	SL	400A A	11	BLK	7.5	9.9	26.3	1565@44	28

** Same Tread Pattern - Branded Grand Spirit Touring SLI (See picture on page 30)

GRAND TOUR SLi - T RATED

LUXURY TOURING

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS.@ PSI	SHIP WEIGHT (lbs.)
SLG24**	185/70R14	88T	SL	620A B	11	BLK	5.5	7.4	24.3	1235@44	18
SLG38**	195/70R14	91T	SL	620A B	11	BLK	6.0	8.1	24.8	1356@44	19
SLG62**	185/65R14	86T	SL	620A B	11	BLK	5.5	7.4	23.5	1168@44	18
GTS22	205/70R15	96T	SL	620A B	11	0.75	6.0	8.2	26.3	1565@44	22
GTS29	205/70R15	96T	SL	620A B	11	BLK	6.0	8.2	26.3	1565@44	22
GTS31	215/70R15	98T	SL	620A B	11	0.75	6.5	8.7	26.9	1653@44	24
GTS33	215/70R15	98T	SL	620A B	11	BLK	6.5	8.7	26.9	1653@44	23
AY-45*	225/70R15	100T	SL	620A B	11	0.75	6.5	9.0	27.4	1764@44	25
GTS27	185/65R15	88T	SL	620A B	11	BLK	5.5	7.4	24.5	1235@44	19
GTT28	195/65R15	91T	SL	620A B	11	BLK	6.0	8.0	24.9	1356@44	20
GTS68	215/65R15	96T	SL	620A B	11	BLK	6.5	8.7	26.0	1565@44	23
GTS73	185/60R15	84T	SL	620A B	11	BLK	5.5	7.4	23.8	1102@44	19
GTT41	195/60R15	88T	SL	620A B	11	BLK	6.0	7.9	24.2	1235@44	19
GTS44	215/60R15	94T	SL	620A B	11	BLK	6.5	8.7	25.2	1477@44	23
AY-54*	205/65R16	95T	SL	620A B	11	BLK	6.0	8.3	26.4	1521@44	23
GTS55	215/65R16	98T	SL	620A B	11	BLK	6.5	8.7	27.0	1653@44	25
GTS48	215/60R16	95T	SL	620A B	11	BLK	6.5	8.7	26.1	1521@44	24
GTS52	225/60R16	98T	SL	620A B	11	BLK	6.5	9.2	26.5	1653@44	25
SLG52**	225/60R16	98T	SL	620A B	11	0.40	6.5	9.2	26.5	1653@44	25
GTT42	205/55R16	91T	SL	620A B	11	BLK	6.5	8.6	24.8	1356@44	23
SLG97**	215/65R17	99T	SL	620A B	11	BLK	6.5	8.9	28.0	1709@44	26
GTS95	215/60R17	96T	SL	620A B	11	BLK	6.5	9.0	27.1	1565@44	25
GTS96	225/60R17	99T	SL	620A B	11	0.40	6.5	9.1	27.6	1709@44	27
GTT88	225/55R17	97T	SL	620A B	11	BLK	7.0	9.3	26.8	1609@44	23

* Slight Differently Tread - Branded Grand Spirit Touring (See picture on page 30)

** Same Tread Pattern - Branded Grand Spirit Touring SLi (See picture on page 30)

ULTREX AS4 TOURING

TOURING ALL SEASON

A HIGH QUALITY TOURING TIRE DESIGNED FOR LONG WEAR, ALL WEATHER TRACTION, AND A SMOOTH COMFORTABLE RIDE. DESIGNED FOR COMPACT CARS, SEDANS, AND MINIVANS.

- Computer Designed All Season Tread For Excellent Performance
- Slotted Shoulders And Circumferential Grooves For Superior Traction
- Tread Rubber Compounds Engineered For Long Even Wear
- Center Rib For Improved Steering Response
- W & M - Free Replacement 1st 50% Treadwear

UTQG: 520 A A



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
AS416	175/70R13	82T	SL	520A A	10	BLK	5.0	6.9	22.6	1047 @ 44	15
AS417	185/70R13	86T	SL	520A A	10	BLK	5.5	7.4	23.2	1168 @ 44	16
AS438	185/75R14	89T	SL	520A A	10	0.65	5.0	7.2	25.0	1279 @ 44	17
AS439	195/75R14	92T	SL	520A A	11	0.65	5.5	7.7	25.5	1389 @ 44	20
AS447	205/75R14	95T	SL	520A A	11	0.65	5.5	8.0	26.1	1521 @ 44	22
AS460	215/75R14	100T	SL	520A A	11	0.65	6.0	8.5	26.7	1653 @ 44	22
AS424	185/70R14	88T	SL	520A A	11	BLK	5.5	7.4	24.2	1235 @ 44	17
AS425	195/70R14	91T	SL	520A A	11	BLK	6.0	7.8	24.8	1356 @ 44	19
AS426	205/70R14	98T	XL	520A A	11	BLK	6.0	8.3	25.6	1521 @ 44	22
AS446	215/70R14	96T	SL	520A A	11	0.65	6.5	8.7	25.9	1565 @ 44	22
AS461	175/65R14	82T	SL	520A A	10	BLK	5.0	6.9	23.0	1047 @ 44	15
AS462	185/65R14	86T	SL	520A A	10	BLK	5.5	7.3	23.4	1168 @ 44	16
AS463	195/65R14	89T	SL	520A A	10	BLK	6.0	7.8	24.0	1279 @ 44	18
AS440	185/60R14	82T	SL	520A A	10	BLK	5.5	7.3	22.8	1047 @ 44	16
AS434	205/75R15	97T	SL	520A A	11	0.75	5.5	8.0	27.1	1609 @ 44	23
AS445	215/75R15	100T	SL	520A A	11	0.75	6.0	8.5	27.7	1764 @ 44	25
AS451	225/75R15	102T	SL	520A A	11	0.75	6.0	8.8	28.3	1874 @ 44	25
AS464	235/75R15	105T	SL	520A A	11	0.75	6.5	9.3	28.9	2039 @ 44	28
AS46C	235/75R15	109T	XL	520A A	11	0.75	6.5	9.3	28.9	2271 @ 50	29
AS429	205/70R15	96T	SL	520A A	11	BLK	6.0	8.3	26.5	1565 @ 44	23
AS433	215/70R15	98T	SL	520A A	11	0.75	6.5	8.7	26.9	1653 @ 44	24
AS449	235/70R15	103T	SL	520A A	11	0.75	7.0	9.4	28.0	1929 @ 44	27
AS428	195/65R15	91T	SL	520A A	10	BLK	6.0	7.8	25.0	1356 @ 44	18
AS430	205/65R15	94T	SL	520A A	10	BLK	6.0	8.2	25.5	1477 @ 44	20
AS468	215/65R15	96T	SL	520A A	11	BLK	6.5	8.7	26.0	1565 @ 44	22
AS441	195/60R15	88T	SL	520A A	10	BLK	6.0	7.9	24.2	1235 @ 44	18
AS443	205/60R15	91T	SL	520A A	10	BLK	6.0	8.2	24.7	1356 @ 44	19
AS444	215/60R15	94T	SL	520A A	11	BLK	6.5	8.7	25.2	1477 @ 44	22
AS437	205/55R15	88T	SL	520A A	10	BLK	6.5	8.4	23.9	1235 @ 44	19
AS455	215/65R16	98T	SL	520A A	11	BLK	6.5	8.7	27.0	1653 @ 44	25
AS448	215/60R16	95T	SL	520A A	11	BLK	6.5	8.7	26.1	1521 @ 44	23
AS452	225/60R16	98T	SL	520A A	11	BLK	6.5	9.0	26.6	1653 @ 44	24
AS442	205/55R16	91T	SL	520A A	10	BLK	6.5	8.4	24.9	1356 @ 44	20

THE ALL SEASON PASSENGER TIRE THAT OFFERS LONG MILEAGE AND DEPENDABILITY IN ALMOST ANY TYPE OF WEATHER.

- All Season Tread Design For Excellent Year Round Traction
- Dual Tread Compound For Longer Wear And Improved Durability
- Variable Tread Element Sequence For A Smooth And Quite Ride

UTQG: 440 A B



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
V2-06*	P155/80R13	STD	SL	440A B	9	0.5	4.5	6.1	22.8	959@35	13
K3-06	P175/70R13	82S	SL	440A B	10	BLK	5.0	6.9	22.7	1036@35	14
Q4-11*	P185/70R13	85S	SL	440A B	10	BLK	5.5	7.4	23.2	1135@35	15
V2-38*	P185/75R14	STD	SL	440A B	10	0.65	5.0	7.2	24.8	1290@35	16
M8-39	P195/75R14	STD	SL	440A B	10	0.65	5.5	7.6	25.4	1400@35	18
M8-47	P205/75R14	STD	SL	440A B	10	0.65	5.5	8.0	26.0	1532@35	19
F2-60**	P215/75R14	STD	SL	340B B	10	0.65	6.0	8.4	26.6	1664@35	20
Q4-21*	P175/70R14	84S	SL	440A B	10	BLK	5.0	6.9	23.2	1102@35	16
K3-35	P185/70R14	87S	SL	440A B	10	BLK	5.5	7.4	24.2	1201@35	17
K3-38	P195/70R14	90S	SL	440A B	10	BLK	6.0	7.8	24.8	1312@35	17
Q4-39*	P205/70R14	93S	SL	440A B	10	BLK	6.0	8.1	25.3	1433@35	18
V2-47*	P215/70R14	96S	SL	440A B	10	0.65	6.5	8.6	25.8	1554@44	21
Q4-61*	P175/65R14	81S	SL	440A B	10	BLK	5.0	6.9	22.9	1019@35	15
Q4-62*	P185/65R14	85S	SL	440A B	10	BLK	5.5	7.4	23.4	1124@35	17
M8-34	P205/75R15	STD	SL	440A B	10	0.75	5.5	8.0	27.0	1598@35	21
M8-45	P215/75R15	STD	SL	440A B	10	0.75	6.0	8.4	27.6	1742@35	22
V2-49*	P225/75R15	STD	SL	440A B	10	0.75	6.0	8.7	28.1	1874@35	23
M8-64	P235/75R15	STD	SL	440A B	11	0.75	6.5	9.1	28.7	2028@35	24
N9-29	P205/70R15	95S	SL	440A B	10	0.75	6.0	8.1	26.3	1499@35	20
K3-29	P205/70R15	95S	SL	440A B	10	BLK	6.0	8.1	26.3	1499@35	20
N9-33	P215/70R15	97S	SL	440A B	10	0.75	6.5	8.6	26.8	1620@35	22
K3-28	P195/65R15	89S	SL	440A B	10	BLK	6.0	7.8	24.9	1279@35	18
K3-44	P205/65R15	92S	SL	440A B	10	BLK	6.0	8.2	25.3	1400@35	20
Q4-65*	P215/65R15	95S	SL	440A B	10	BLK	6.5	8.7	25.9	1510@44	22
7V-29	P215/60R16	94S	SL	440A B	10	BLK	6.5	8.6	26.1	1477@35	22
7V-52	P225/60R16	97S	SL	440A B	10	BLK	6.5	8.8	26.5	1609@35	23
7V-37	P205/55R16	89S	SL	440A B	10	BLK	6.5	8.3	24.8	1279@35	22

* Branded Classic Radial (See picture on page 30)

** Slightly Different Tread Design - Branded Radial XL (See picture on page 30)

EPIC TOUR

VALUE ALL SEASON

OFFERING RELIABLE ALL SEASON TRACTION WITH A TOURING TIRE LOOK.
AVAILABLE IN SOME OF THE MOST POPULAR T SPEED RATING SIZES.

- All Season Tread Design For Dependable Performance
- Center Rib For Ride Comfort, Traction, And Steering Response
- T & H Performance Rated

UTQG: 440 A A / 440 A B



CLASSIC ALL SEASON

EPIC TOUR

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
CPT05*	155/80R12	77T	SL	NA#	8	BLK	4.5	6.2	21.8	908 @ 44	13
CPT08*	165/80R15	87T	SL	280B B	8	BLK	4.5	6.9	25.5	1202 @ 44	16
EPT06	175/70R13	82S	SL	440A B	9	BLK	5.0	6.9	22.8	1047 @ 35	15
EPT11	185/70R13	85S	SL	440A B	9	BLK	5.5	7.2	23.2	1135 @ 35	16
EPT21	175/70R14	84S	SL	440A B	9	BLK	5.0	6.8	23.8	1102 @ 35	16
EPT23	185/70R14	87S	SL	440A B	9	BLK	5.5	7.2	24.4	1201 @ 35	18
EPT38	195/70R14	90S	SL	440A B	9	BLK	6.0	7.9	24.8	1323 @ 35	19
EPT39	205/70R14	93S	SL	440B B	9	BLK	6.0	8.2	25.3	1433 @ 35	23
EPT47	215/70R14	96S	SL	440B B	10	BLK	6.5	8.8	25.9	1565 @ 35	23
EPT61	175/65R14	81T	SL	440A A	10	BLK	5.0	6.8	22.9	1019 @ 35	15
EPT62	185/65R14	85T	SL	440A A	10	BLK	5.5	7.2	23.5	1135 @ 35	18
EPT36	185/60R14	82T	SL	440A A	10	BLK	5.5	7.1	22.9	1047 @ 35	17
EPT35	195/60R14	85T	SL	440A A	10	BLK	6.0	7.6	23.2	1135 @ 35	18
EPT29	205/70R15	95S	SL	440B B	9	BLK	6.0	8.1	26.4	1521 @ 35	23
EPT33	215/70R15	97S	SL	440B B	10	BLK	6.5	8.8	26.8	1609 @ 35	24
EPT71	185/65R15	86T	SL	440A A	10	BLK	5.5	7.1	24.5	1168 @ 35	19
EPT28	195/65R15	89T	SL	440A A	10	BLK	6.0	7.6	25.0	1279 @ 35	20
EPT44	205/65R15	92T	SL	440A A	10	BLK	6.0	8.1	25.5	1389 @ 35	22
EPT68	215/65R15	95T	SL	440A A	11	BLK	6.5	8.4	26.0	1521 @ 35	24
EPT40	195/60R15	87T	SL	440A A	10	BLK	6.0	7.7	24.3	1201 @ 35	20
EPT43	205/60R15	90T	SL	440A A	10	BLK	6.0	8.1	24.6	1323 @ 35	22
EPT22	215/60R15	94T	SL	440A A	11	BLK	6.5	8.5	25.2	1477 @ 35	22
EPT55	215/65R16	96T	SL	440A A	11	BLK	6.5	8.5	27.0	1565 @ 35	25
EPT19	205/60R16	92T	SL	440A A	11	BLK	6.0	8.0	25.7	1389 @ 35	21
EPT48	215/60R16	94T	SL	440A A	11	BLK	6.5	8.2	26.1	1477 @ 35	24
EPT52	225/60R16	97T	SL	440A A	11	BLK	6.5	8.8	26.6	1609 @ 35	26
EPT41	205/55R16	89H	SL	440A A	9	BLK	6.5	8.1	24.9	1279 @ 35	21
EPT57	215/55R16	93T	SL	440A A	11	BLK	7.0	8.8	25.3	1356 @ 35	22

* 4 Rib Design Branded Classic All Season, Available 2nd Quarter 2009

12" Tires Are Not Required To Have UTQG Rating

CUSTOM 428+

VALUE ALL SEASON

PROVEN ALL SEASON DESIGN AND TRACTION AT AN ECONOMY PRICE.

- *All Season Tread Pattern For Dependable Service*
- *M & S Rated*
- *Black Sidewall*

UTQG: 440 A B



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
B1P06	155/80R13	79T	SL	440A B	9	BLK	4.5	6.2	22.8	959 @ 44	14
B1P38	185/75R14	89T	SL	440A B	9	BLK	5.0	7.3	25.0	1290 @ 44	18
B1P39	195/75R14	92T	SL	440A B	9	BLK	5.5	7.7	25.5	1400 @ 44	19
B1P47	205/75R14	95T	SL	440A B	10	BLK	5.5	8.0	26.2	1532 @ 44	21
B1P34	205/75R15	97T	SL	440A B	10	BLK	5.5	8.0	27.2	1598 @ 44	23
B1P45	215/75R15	100T	SL	440A B	10	BLK	6.0	8.5	27.7	1742 @ 44	23
B1P49	225/75R15	102T	SL	440A B	10	BLK	6.0	8.8	28.3	1874 @ 44	25
B1P64	235/75R15	105T	SL	440A B	10	BLK	6.5	9.3	28.9	2028 @ 44	28
B1P6C	235/75R15	109T	XL	440A B	10	BLK	6.5	9.3	28.9	2271 @ 45	29
B1P29	205/70R15	95T	SL	440A B	10	BLK	6.0	8.3	26.4	1499 @ 44	22
B1P33	215/70R15	97T	SL	440A B	10	BLK	6.5	8.7	26.9	1620 @ 44	24
B1P30	205/65R15	92T	SL	440A B	10	BLK	6.0	8.2	25.5	1400 @ 44	22
B1P52	225/60R16	97T	SL	440A B	11	BLK	6.5	9.0	26.6	1609 @ 44	26

HTR SPORT H/P

SPORT LIGHT TRUCK

COMBINING A PASSENGER CAR RIDE WITH SPORTS CAR PERFORMANCE. ENGINEERED TO PROVIDE HIGH PERFORMANCE IN ALL SEASONS WITH AN EYE-CATCHING APPEARANCE.

- *Non-Directional All Season Tread Pattern For Superior Traction*
- *Center Rib For Greater Straight Line Stability*
- *Designed For The Load Requirements Of SUV's And Light Trucks*
- *Wheel Flange Guard - Protects Wheel Rim From Curb Damage*
- *Alternative Sidewall Styling: Smooth On One Side And Stylish Serrated Design On Opposite Sidewall*

UTQG: 480 A A



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS.@ PSI	SHIP WEIGHT (lbs.)
5521412	285/60R18	116H	SL	480A A	14	BLK	8.5	11.5	31.5	2756@51	49
5521421	255/55R18	109H	XL	480A A	14	BLK	8.0	10.0	29.0	2271@50	40
5521416	P275/60R20	114H	SL	480A A	14	BLK	8.0	10.9	33.0	2601@51	47
5521426	275/55R20	117H	SL	480A A	14	BLK	8.5	11.0	32.1	2833@50	45
5521435	285/50R20	116H	XL	480A A	14	BLK	9.0	11.2	31.3	2756@50	45
5521437	305/50R20	120H	XL	480A A	14	BLK	9.5	12.0	32.0	3086@50	50
5521448	275/45R20	110H	XL	480A A	14	BLK	9.0	10.6	29.8	2337@50	40
5521450	P295/45R20	114H	XL	480A A	14	BLK	10.0	11.6	30.4	2601@50	44
5521454	285/45R22	114H	SL	480A A	14	BLK	9.5	11.1	32.0	2601@50	43
5521458	P305/45R22	118H	XL	480A A	14	BLK	10.0	12.0	32.8	2910@50	53
5521462	265/40R22	106H	SL	480A A	14	BLK	9.5	10.6	30.3	2094@50	38
5521468	305/40R22	114H	XL	480A A	14	BLK	11.0	12.3	31.6	2601@50	49
5521480	265/35R22	102H	SL	480A A	14	BLK	9.5	10.6	29.3	1874@50	36
5521482	285/35R22	106H	XL	480A A	14	BLK	10.0	11.2	29.9	2094@50	40
5521490	295/35R24	110H	SL	480A A	14	BLK	10.5	11.7	32.2	2337@50	44
5521492	305/35R24	112H	SL	480A A	14	BLK	11.0	12.2	32.4	2469@50	47

MIRADA CROSS TOUR SLX

TOURING CUV/SUV

A TIRE THAT WAS DESIGNED TO MEET THE MANY CHANGING NEEDS OF TODAY'S CROSSOVER AND SUV OWNERS. THIS VERSATILE TIRE BLENDS THE RUGGED BUILD OF A LIGHT TRUCK TIRE WITH THE EXCEPTIONAL RIDE QUALITY AND ROAD MANNERS OF A TOURING TIRE.

- Five Circumferential Grooves To Resist Hydroplaning
- Interlocking Center Ribs For Crisp Handling And Even Wear
- Notched Support Ribs For Exception Steering Response
- Advanced Silica Tread For Wet Traction And Long Tread Wear
- Optimized Tread Design With Wave Like Sections For A Quiet Ride And Impressive Traction
- W & M - Free Replacement 1st 50% Treadwear
- Free Consumer Roadside Assistance Warranty

UTQG: 640 A B (S, T Rated)
640 A A (H, V Rated)



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
CUV64	235/75R15	105S	SL	640 A B	11	OWL	6.5	9.4	28.7	2039 @ 51	31
CUV75	225/75R16	104S	SL	640 A B	11	OWL	6.0	8.7	29.3	1984 @ 51	33
CUV79	245/75R16	111S	SL	640 A B	11	OWL	7.0	9.8	30.2	2403 @ 51	37
CUV81	265/75R16	116S	SL	640 A B	12	OWL	7.5	10.6	31.3	2756 @ 51	39
CUV48	215/70R16	100T	SL	640 A B	11	BSW	6.5	8.7	28.0	1764 @ 51	27
CUV77	225/70R16	103S	SL	640 A B	11	OWL	6.5	8.9	28.1	1929 @ 51	29
CUV53	235/70R16	106S	SL	640 A B	11	OWL	7.0	9.5	28.6	2094 @ 51	31
CUV80	245/70R16	107S	SL	640 A B	11	OWL	7.0	9.7	29.2	2149 @ 51	33
CUV86	255/70R16	111S	SL	640 A B	12	OWL	7.5	10.2	29.8	2403 @ 51	35
CUV93	265/70R16	112S	SL	640 A B	12	OWL	8.0	10.7	30.2	2469 @ 51	37
CUV99	235/65R16	103S	SL	640 A B	11	OWL	7.0	9.7	28.0	1929 @ 51	31
CUV89	245/70R17	110S	SL	640 A B	12	OWL	7.0	10.0	30.3	2337 @ 51	40
CUV87	265/70R17	115S	SL	640 A B	12	OWL	8.0	10.6	31.3	2679 @ 51	38
CUV76	225/65R17	102T	SL	640 A B	11	BSW	6.5	8.9	28.6	1874 @ 51	29
CUV82	235/65R17	104H	SL	640 A A	11	BSW	7.0	9.4	28.9	1984 @ 51	33
CUV67	245/65R17	107T	SL	640 A B	11	BSW	7.0	9.8	29.4	2149 @ 51	34
CUV59	265/65R17	112T	SL	640 A B	12	BSW	8.0	10.8	30.2	2469 @ 51	42
CUV07	235/60R17	102T	SL	640 A B	11	BSW	7.0	9.3	28.3	1874 @ 51	31
CUV61	235/65R18	106T	SL	640 A B	11	BSW	7.0	9.4	29.9	2094 @ 51	33
CUV08	235/60R18	107H	SL	640 A A	11	BSW	7.0	9.3	29.0	2149 @ 50	30
CUV65	245/60R18	105T	SL	640 A B	11	BSW	7.0	9.8	29.4	2039 @ 51	33
CUV91	265/60R18	110T	SL	640 A B	12	BSW	8.0	10.7	30.3	2337 @ 51	42
CUV03	235/55R18	100V	SL	640 A A	11	BSW	7.5	9.6	28.0	1764 @ 51	29

WILD COUNTRY SPORT H/T

PREMIUM ALL SEASON SUV/LT

THE PERFECT O.E. UPGRADE, COMBINING THE SMOOTH RIDE OF AN ALL WEATHER TOURING TIRE WITH THE STRENGTH AND DURABILITY OF A LIGHT TRUCK TIRE. DESIGNED TO MEET THE NEED OF TODAY'S CROSSOVERS, SUV'S, PICK-UPS & VANS.

- Computer Generated All Season Tread Design For All Weather Performance
- Wide Circumferential Grooves For Excellent On-Road Comfort And Responsiveness
- Slotted Shoulder And Lateral Slots Provide Exceptional Wet, Dry, And Snow Traction
- Solid Center Rib For Improved Steering Response
- 65,000 Mile / 60 Month Mileage Warranty (Metric Only)

UTQG: 540 A B (Metric Only)



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	MAX. LOAD LBS. @ PSI		SHIP WEIGHT (lbs.)
										SINGLE	DUAL	
WSH51*	225/75R15	102S	SL	540A B	13	OWL	6.0	9.0	28.2	1874@44	—	27
WCH64	235/75R15	105S	SL	540A B	13	OWL	6.5	9.3	28.9	2039@44	—	29
WSH50*	265/75R15	112S	SL	540A B	14	OWL	7.5	10.7	30.5	2469@44	—	37
WSH96*	225/70R15	100S	SL	540A B	12	OWL	6.5	9.1	27.3	1764@44	—	27
WCH49	235/70R15	103S	SL	540A B	12	OWL	7.0	9.7	27.8	1929@44	—	29
WCH91	265/70R15	112S	SL	540A B	13	OWL	8.0	10.5	29.4	2469@44	—	35
WCH75	225/75R16	104S	SL	540A B	13	OWL	6.0	8.7	29.2	1984@44	—	30
WCH78	235/75R16	108S	SL	540A B	13	OWL	6.5	9.3	29.7	2205@44	—	33
WCH79	245/75R16	111S	SL	540A B	13	OWL	7.0	9.6	30.4	2403@44	—	35
WCH81	265/75R16	116S	SL	540A B	14	OWL	7.5	10.6	31.5	2756@44	—	40
WCH48	215/70R16	100S	SL	540A B	12	BLK	6.5	8.8	27.8	1764@44	—	28
WCH77	225/70R16	103S	SL	540A B	13	OWL	6.5	9.0	28.3	1929@44	—	30
WCH53	235/70R16	106T	SL	540A B	13	OWL	7.0	9.4	28.9	2094@44	—	33
WCH80	245/70R16	107S	SL	540A B	13	OWL	7.0	9.9	29.4	2149@44	—	34
WCH86	255/70R16	111S	SL	540A B	13	OWL	7.5	10.3	30.0	2403@44	—	36
WCH93	265/70R16	112S	SL	540A B	13	OWL	8.0	10.8	30.4	2469@44	—	37
WCH99	235/65R16	103T	SL	540A B	11	BLK	7.0	9.6	27.9	1929@44	—	26
WCH65	255/65R16	109S	SL	540A B	12	OWL	7.5	10.2	29.1	2271@44	—	32
WCH89	245/70R17	110S	SL	540A B	12	OWL	7.0	10.0	30.4	2337@44	—	36
WCH87	265/70R17	115S	SL	540A B	13	OWL	8.0	10.7	31.4	2679@44	—	40
WCH82	235/65R17	104S	SL	540A B	12	OWL	7.0	9.5	29.1	1984@44	—	31
WCH67	245/65R17	107S	SL	540A B	13	OWL	7.0	9.6	29.5	2149@44	—	33
WSH12*	LT235/75R15	104/101Q	C	—	16	OWL	6.5	9.0	28.8	1985@50	1820@50	34
WSH36*	LT245/75R16	108/104Q	C	—	16	OWL	7.0	9.6	30.4	2205@50	2006@50	41
WSH38*	LT245/75R16	120/116Q	E	—	16	BLK	7.0	9.6	30.4	3042@80	2778@80	45
WSH32*	LT265/75R16	112/109Q	C	—	16	OWL	7.5	10.3	31.6	2470@50	2270@50	43
WSH39*	LT265/75R16	123/120Q	E	—	16	OWL	7.5	10.3	31.6	3415@80	3085@80	47
WSH70*	LT245/70R17	119/116R	E	—	16	BLK	7.0	9.6	30.6	3000@80	2755@80	45

* Same Tread Design - Branded Wild Spirit Sport H/T (See picture on page 31)

WILD COUNTRY RADIAL XTX Sport

PREMIUM ALL TERRAIN SUV/LT

A PREMIUM ALL TERRAIN TIRE WITH OUTSTANDING ON-ROAD AND OFF-ROAD PERFORMANCE. A TIRE THAT PERFORMS AS WELL ON, AS OFF ROAD. TRACTION, COMFORT, AND A QUIET RIDE PACKAGED IN AN AGGRESSIVE LOOKING ALL TERRAIN TIRE. THE WILD COUNTRY XTX SPORT CARRIES THE RMA SEVERE SNOW SYMBOL PROVING ITS SUPERIOR TRACTION.

- *Computer Generated Tread Design For Superior All-Terrain Performance*
- *Deep, Aggressive Tread, With Lateral Slots And Notched Elements For Exceptional Traction*
- *Variable Tread Element Positioning For A Quieter Smoother Ride*
- *Wrap Around Shoulder Elements Provide For Improved Traction On Soft Surfaces*
- *Carries RMA Severe Snow Symbol For Superior Winter Traction*
- *Optimized Tread Profile For Improved Wear And Handling*
- *50,000 Mile/48 Month Mileage Warranty (P-Metric Only)*



Meets the Severe Snow Requirement of the Rubber Manufacturers Association (RMA)

UTQG: 500 A B

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
XTS64	235/75R15	105S	SL	500A B	14	OWL	6.5	9.2	28.9	2039@44	30
XTS50	265/75R15	112S	SL	500A B	14	OWL	7.5	10.5	30.7	2469@44	37
XTS49	235/70R15	103S	SL	500A B	12	OWL	7.0	9.5	28.0	1929@44	29
FJ-91*	265/70R15	112S	SL	500A B	14	OWL	8.0	10.6	29.6	2469@44	36
XTS75	225/75R16	104S	SL	500A B	13	OWL	6.0	8.7	29.3	1984@44	30
XTS76	235/75R16	108S	SL	500A B	14	OWL	6.5	9.3	29.8	2205@44	33
XTS79	245/75R16	111S	SL	500A B	14	OWL	7.0	9.7	30.5	2403@44	34
XTS81	265/75R16	116S	SL	500A B	14	OWL	7.5	10.5	31.7	2756@44	38
XTS48	215/70R16	100S	SL	500A B	13	OWL	6.5	8.7	27.9	1764@44	28
XTS71	225/70R16	103S	SL	500A B	13	OWL	6.5	8.9	28.4	1929@44	30
XTS53	235/70R16	106T	SL	500A B	14	OWL	7.0	9.5	29.0	2094@44	33
XTS80	245/70R16	107S	SL	500A B	13	OWL	7.0	9.8	29.6	2149@44	33
XTS86	255/70R16	111S	SL	500A B	14	OWL	7.5	10.2	30.1	2403@44	35
XTS93	265/70R16	112T	SL	500A B	14	OWL	8.0	10.9	30.5	2469@44	37
WST09**	235/70R17	111S	SL	500A B	14	OWL	7.0	9.5	30.0	2403@44	24
XTS89	245/70R17	110S	SL	500A B	14	OWL	7.0	10.1	30.4	2337@44	35
XTS87	265/70R17	115S	SL	500A B	14	OWL	8.0	10.7	31.6	2679@44	39
XTS82	235/65R17	104T	SL	500A B	13	OWL	7.0	9.5	29.1	1984@44	32
XTS67	245/65R17	107S	SL	500A B	13	OWL	7.0	9.6	29.6	2149@44	34
WST20**	255/65R17	110S	SL	500A B	13	OWL	7.5	9.9	30.1	2337@44	36
XTS59	265/65R17	112T	SL	500A B	13	OWL	8.0	10.7	30.6	2470@44	38
XTS22	265/70R18	116S	SL	500A B	14	OWL	8.0	10.7	32.6	2756@44	43
XTS73	275/55R20	117S	XL	500A B	13	OWL	8.5	12.7	31.9	2833@50	45

* Slightly Different Tread Design - Branded Wild Spirit Radial A/T (See picture on page 31)

** Same Tread Design - Branded Wild Spirit Radial AT/S (See picture on page 31)

WILD COUNTRY RADIAL XTX^{SPORT}

PREMIUM ALL TERRAIN SUV/LT

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	MAX. LOAD LBS. @ PSI		SHIP WEIGHT (lbs.)
									SINGLE	DUAL	
XTS12	LT235/75R15	104/101R	C	16	OWL	6.5	9.2	28.9	1985@50	1820@50	34
XTS15	LT215/85R16	115/112R	E	16	BLK	6.0	8.4	30.3	2680@80	2470@80	38
XTS17	LT235/85R16	120/116R	E	16	BLK	6.5	9.4	31.8	3042@80	2778@80	42
XTS26	LT225/75R16	115/112R	E	16	BLK	6.0	8.9	29.4	2680@80	2470@80	38
XTS36	LT245/75R16	108/104R	C	16	OWL	7.0	9.6	30.5	2205@50	2006@50	42
XTS38	LT245/75R16	120/116R	E	16	OWL	7.0	9.3	30.4	3042@80	2778@80	43
XTS32	LT265/75R16	112/109R	C	16	OWL	7.5	10.5	31.6	2470@50	2270@50	47
XTS39	LT265/75R16	123/120R	E	16	OWL	7.5	10.6	31.6	3415@80	3085@80	48
XTS88	LT285/75R16	122/119R	D	17	OWL	8.0	11.5	32.6	3305@65	3000@65	52
XTS77	LT315/75R16	121R	D	17	OWL	8.5	12.4	34.5	3195@50	-	62
XTS55	LT255/70R16	108/104R	C	16	OWL	7.5	10.4	30.1	2205@50	1985@50	43
FJ-98*	LT305/70R16	118/115Q	D	17	BLK	9.0	12.2	32.8	2910@50	2680@50	59
XTS95	LT235/80R17	120/117R	E	16	BLK	6.5	9.2	31.8	3085@80	2835@80	43
WST19**	LT245/75R17	121/118S	E	16	OWL	7.0	10.0	31.5	3195@80	2910@80	46
XTS90	LT265/70R17	112/109R	C	16	OWL	8.0	10.6	31.6	2470@50	2270@50	48
XTS91	LT265/70R17	121/118R	E	16	OWL	8.0	10.9	31.6	3195@80	2910@80	49
XTS83	LT285/70R17	121/118R	D	17	OWL	8.5	11.7	32.8	3195@65	2910@65	52
XTS72	LT275/70R18	125/122S	E	16	OWL	8.0	11.1	33.2	3640@80	3305@80	54
WST40**	LT275/65R18	123/120S	E	16	OWL	8.0	11.1	32.1	3415@80	3085@80	52
XTS78	30X9.50R15LT	104R	C	16	OWL	7.5	9.6	29.3	1985@50	-	37
XTS44	31X10.50R15LT	109R	C	16	OWL	8.5	10.7	30.3	2270@50	-	40
XTS41	32X11.50R15LT	113R	C	17	OWL	9.0	11.4	31.5	2535@50	-	45
XTS33	33X12.50R15LT	108R	C	17	OWL	10.0	12.5	32.5	2205@35	-	50

* Slightly Different Tread Design - Branded Wild Spirit Radial A/T (See picture on page 31)

** Same Tread Design - Branded Wild Spirit Radial AT/S (See picture on page 31)



Meets the Severe Snow Requirement of the Rubber Manufacturers Association (RMA)

WILD COUNTRY RADIAL XRT™

ALL POSITION / ALL TERRAIN - SUV/LT

A VERSATILE ALL SEASON TIRE WITH OFF-ROAD CAPABILITIES. AN ALL PURPOSE TIRE AVAILABLE IN SIZING FOR BOTH SUV'S, PICK-UPS AND VANS.

- Five Rib All Season Design Provides Excellent Traction
- Lateral Grooves And Slots Provide Improved Wet Weather Traction
- Center Rib For Good Steering Response And Long Even Highway Wear
- Rigid Lower Sidewall Enhances Handling And Stability
- Alternating Tread Elements For A Quieter Ride

UTQG: 400 A B



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
U5-45	215/75R15	100S	SL	400A B	11	OWL	6.0	8.6	27.5	1764@44	24
U5-49	225/75R15	102S	SL	400A B	11	OWL	6.0	9.0	28.1	1874@44	26
U5-64	235/75R15	105S	SL	400A B	11	OWL	6.5	9.3	28.7	2039@44	28
U5-6C	235/75R15	109S	XL	400A B	11	OWL	6.5	9.3	28.9	2271@41	31
U5-50	265/75R15	112S	SL	400A B	11	OWL	7.5	10.7	30.4	2469@44	35
U5-79	245/75R16	111S	SL	400A B	11	OWL	7.0	9.8	30.2	2403@44	33
U5-81	265/75R16	116S	SL	400A B	11	OWL	7.5	10.6	31.3	2756@44	37
U5-77	225/70R16	103S	SL	400A B	11	OWL	6.5	9.1	28.2	1929@44	29
U5-53	235/70R16	106S	SL	400A B	11	OWL	7.0	9.4	28.7	2094@44	31
U5-80	245/70R16	107S	SL	400A B	11	OWL	7.0	9.9	29.4	2149@44	32
U5-86	255/70R16	111S	SL	400A B	11	OWL	7.5	10.3	29.8	2403@44	34
U5-93	265/70R16	112S	SL	400A B	11	OWL	8.0	10.8	30.2	2469@44	38

• NOTE: LT Sizes Continued On Next Page

WILD COUNTRY RADIAL XRT™

ALL POSITION / ALL TERRAIN - SUV/LT

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	MAX. LOAD LBS. @ PSI		SHIP WEIGHT (lbs.)
									SINGLE	DUAL	
U5-12	LT235/75R15	104/101Q	C	14	OWL	6.5	8.9	28.7	1985@50	1820@50	31
U5-17	LT235/85R16	120/116N	E	14	BLK	6.5	9.3	31.5	3042@80	2778@80	40
U5-25	LT225/75R16	115/112Q	E	14	BLK	6.0	8.5	29.3	2680@80	2470@80	36
U5-38	LT245/75R16	120/116N	E	14	BLK	7.0	9.4	30.4	3042@80	2778@80	39
U5-32	LT265/75R16	112/109N	C	14	OWL	7.5	10.4	31.6	2470@50	2270@50	43
U5-78	30X9.50R15LT	104Q	C	14	OWL	7.5	9.3	29.1	1985@50	-	33
U5-44	31X10.50R15LT	109Q	C	14	OWL	8.5	10.5	30.0	2270@50	-	37
ET-15*	LT215/85R16	115/112Q	E	14	BLK	6.0	8.4	30.2	2680@80	2470@80	37
ET-17*	LT235/85R16	120/116N	E	14	BLK	6.5	9.3	31.5	3042@80	2778@80	40
ET-25*	LT225/75R16	115/112Q	E	14	BLK	6.0	8.5	29.3	2680@80	2470@80	36
ET-38*	LT245/75R16	120/116N	E	14	BLK	7.0	9.4	30.4	3042@80	2778@80	39
ET-58*	8.75R16.5LT	111/106N	D	14	BLK	6.8	8.6	29.5	2405@65	2095@65	34
ET-60*	9.50R16.5LT	117/112N	D	14	BLK	6.8	9.2	30.3	2835@65	2470@65	38

* Branded Power King Radial A/S - Slightly Different Tread Design (See picture on page 31)

TRAIL GUIDE AP

VALUE ALL TERRAIN - SUV/LT

A VALUE PRICE ALL SEASON, ALL TERRAIN TIRE AVAILABLE IN SIZING FOR BOTH SUV'S, AND PICK-UPS.

- All Terrain Tread Design For Dependable Traction
- Wide Circumferential Grooves For Improved Wet Traction
- Variable Pitch Sequence For A Quieter Ride
- Center Rib For Long Even Highway Wear

UTQG: 400 A B



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
TGR64	235/75R15	105S	SL	400A B	11	OWL	6.5	9.3	28.7	2039 @ 44	34
TBD	245/75R16	111S	SL	400A B	11	OWL	-	-	-	2403 @ 44	-
TBD	265/75R16	116S	SL	400A B	11	OWL	-	-	-	2756 @ 44	-
TGR53	235/70R16	106S	SL	400A B	11	OWL	7.0	9.4	28.7	2094 @ 44	35
TGR80	245/70R16	107S	SL	400A B	11	OWL	7.0	9.9	29.4	2149 @ 44	38
TGR86	255/70R16	111S	SL	400A B	11	OWL	7.5	10.3	29.8	2403 @ 44	39
TGR93	265/70R16	112S	SL	400A B	11	OWL	8.0	10.8	30.2	2469 @ 44	41
TBD	245/70R17	110S	SL	400A B	11	OWL	-	-	-	2337 @ 44	-
TBD	265/70R17	115S	SL	400A B	11	OWL	-	-	-	2679 @ 44	-
TBD	235/65R17	104S	SL	400A B	11	OWL	-	-	-	1984 @ 44	-
TBD	245/65R17	107S	SL	400A B	11	OWL	-	-	-	2149 @ 44	-

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	MAX. LOAD LBS. @ PSI		SHIP WEIGHT (lbs.)
									SINGLE	DUAL	
TGR15	LT235/75R15	115/112Q	E	14	OWL	6.5	8.9	28.7	1985@50	1820 @ 50	39.2
TGR17	LT235/85R16	120/116Q	E	14	BLK	6.5	9.3	31.5	3042@80	2778 @ 80	43.1
TGR26	LT225/75R16	115/112Q	E	14	BLK	6.0	8.5	29.3	2680@80	2470 @ 80	38.9
TGR38	LT245/75R16	120/116Q	E	14	OWL	7.0	9.4	30.4	3042@80	2778 @ 80	44.0
TGR39	LT265/75R16	123/120Q	E	14	OWL	7.5	10.5	31.7	3415@80	3085 @ 80	48.2
TGR44	31X10.50R15	109Q	C	14	OWL	8.5	10.5	30.0	2270@50		45.5
TBD	LT265/70R17	121/118Q	E	14	OWL	-	-	-	3197 @ 80	2910 @ 80	-

TBD: Sizes to be released in June 2009. Specification detail not available at time of printing.

POWER KING LT RADIAL HWY

PREMIUM COMMERCIAL HIGHWAY

A PREMIUM HEAVY DUTY HIGHWAY TIRE PERFECT FOR COMMERCIAL APPLICATIONS REQUIRING A LONG WEARING TRUCK TIRE THAT CAN HAUL OR TOW ALMOST ANYTHING.

- *5-Rib Tread Design For Improved Handling*
- *Solid Shoulders Promote Long Even Wear*
- *Wide Circumferential Grooves For Greater Wet Weather Traction*
- *Tread Design For Smooth Durable Highway Performance*
- *Center Rib For Superior Stability*



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	MAX. LOAD LBS. @ PSI		SHIP WEIGHT (lbs.)
									SINGLE	DUAL	
NY-15	LT215/85R16	115/112N	E	14	BLK	6.0	8.2	30.3	2680@80	2470@80	39
NY-17	LT235/85R16	120/116N	E	14	BLK	6.5	9.2	31.7	3042@80	2778@80	42
NY-26	LT225/75R16	115/112N	E	14	BLK	6.0	8.6	29.2	2680@80	2470@80	39
NY-38	LT245/75R16	120/116N	E	16	BLK	7.0	9.4	30.5	3042@80	2778@80	42
NY-39	LT265/75R16	123/120N	E	14	BLK	7.5	10.5	31.7	3415@80	3085@80	47
NY-49	7.50R16LT	112/107N	D	14	BLK	6.0	8.4	31.8	2470@65	2150@65	37
NY-57	8.00R16.5LT	105/101N	D	14	BLK	6.0	7.8	28.5	2040@65	1820@65	34
NY-58	8.75R16.5LT	111/106N	D	14	BLK	6.8	8.7	29.4	2405@65	2095@65	38
NY-60	9.50R16.5LT	117/112N	D	14	BLK	6.8	9.2	30.4	2835@65	2470@65	40
GX-61*	8R19.5	124/122K	F	16	BLK	6.0	8.0	33.9	3500@110	3070@110	67

* Branded TR656 And Has An All Steel Cord Body Ply Construction.

SOLID TRAC RADIAL A/S

COMMERCIAL HIGHWAY ALL SEASON

ALL-SEASON HIGHWAY RIB PROVIDING DEPENDABLE TRACTION AND LONG WEAR. QUALITY AT A VALUE PRICE.

- 5-Rib All Season Tread Design For Excellent Traction
- Alternating Shoulder Slots For Improved Wear And All Season Performance
- Four Circumferential Grooves For Improved Traction
- Large Shoulder Elements To Promote Long Even Wear
- Center Rib For Good Steering Response



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	MAX. LOAD LBS. @ PSI		SHIP WEIGHT (lbs.)
									SINGLE	DUAL	
STR12	LT235/75R15	104/101Q	C	15	BLK	6.5	9.6	29.3	1985@50	1820@50	34
STR15	LT215/85R16	115/112Q	E	15	BLK	6.0	8.5	30.4	2680@80	2470@80	39
STR17	LT235/85R16	120/116Q	E	15	BLK	6.5	9.3	31.7	3042@80	2778@80	44
STR18*	LT235/85R16	126/123Q	G	15	BLK	6.5	9.3	31.7	3750@110	3415@110	47
STR25	LT225/75R16	115/112Q	E	15	BLK	6.0	8.8	29.3	2680@80	2470@80	37
STR38	LT245/75R16	120/116Q	E	15	BLK	7.0	9.8	30.5	3042@80	2778@80	44
STR39	LT265/75R16	123/120Q	E	15	BLK	7.5	10.5	31.7	3415@80	3085@80	48

* Requires High Capacity Wheel - 110 PSI Capacity

TRIANGLE TR645

LIGHT VAN RADIAL COMMERCIAL HIGHWAY

ALL-SEASON AND ALL POSITION RADIAL FOR VANS AND TRANSPORTERS.

- *Multi-Purpose Design For Light Trucks, Minivans, And Utility Vehicles*
- *Long Wearing All-Position Steel Belted Radial*
- *Deep Tread For Traction And Long Wear*
- *8 Ply Tire For Strength And Durability*
- *Tubeless*



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	SINGLE MAX. LOAD LBS.@ PSI	SHIP WEIGHT (lbs.)
S3-30	185R14C	102/100S	D	13	BLK	5.5	7.4	25.7	1850@65	23	23
S3-31	195R14C	106/104S	D	14	BLK	5.5	7.8	26.3	2060@65	26	26

WILD SPIRIT RADIAL TXR^{LT}

COMMERCIAL TRACTION - LT

HEAVY-DUTY TRACTION, AND DURABILITY TO MEET THE DEMANDING NEEDS OF COMMERCIAL APPLICATIONS.

- All Weather Tread Compound For Excellent Performance In All Seasons, And All Surfaces
- Unique Shoulder Lugs And A Deep Tread Provide Extra Grip For Outstanding On Or Off-Road Traction
- Outer Tread Blocks Are Pinned For Studs For Incredible Ice And Snow Traction
- Premium "Truck" Duty Casing Design Provides Extra Load Carrying Capacity
- Staggered Tread Elements Improve Wear And Provide A Quieter Ride



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	MAX. LOAD LBS. @ PSI		SHIP WEIGHT (lbs.)
									SINGLE	DUAL	
TXR64	235/75R15	105S	SL	15	OWL	6.5	9.4	29.0	2039@44	-	32
TXR12	LT235/75R15	104/101Q	C	18	OWL	6.5	9.1	28.6	1985@50	1820@50	37
TXR17	LT235/85R16	120/116N	E	18	BLK	6.5	9.3	31.9	3042@80	2778@80	45
TXR85	LT255/85R16	119/116N	D	18	OWL	7.0	10.0	33.2	3000@65	2755@65	48
TXR25	LT225/75R16	115/112N	E	18	BLK	6.0	8.5	29.4	2680@80	2470@80	40
TXR38	LT245/75R16	120/116N	E	18	BLK	7.0	9.8	30.5	3042@80	2778@80	46
TXR32	LT265/75R16	112/109N	C	18	OWL	7.5	10.5	31.6	2470@50	2270@50	46
TXR39	LT265/75R16	123/120N	E	18	OWL	7.5	10.6	31.8	3415@80	3085@80	51
TXR88	LT285/75R16	122/119N	D	20	OWL	8.0	11.3	32.8	3305@65	3000@65	57
TXR77	LT315/75R16	121N	D	20	OWL	8.5	12.9	34.6	3195@50	-	67
TXR95	LT235/80R17	120/117Q	E	18	OWL	6.5	9.4	31.9	3085@80	2835@80	47
TXR90	LT265/70R17	112/109Q	C	18	OWL	8.0	10.7	31.7	2470@50	2270@50	47
TXR91	LT265/70R17	121/118Q	E	18	OWL	8.0	11.0	31.7	3195@80	2910@80	52
TXR78	30X9.50R15LT	104Q	C	18	OWL	7.5	9.6	29.4	1985@50	-	37
TXR44	31X10.50R15LT	109Q	C	18	OWL	8.5	10.7	30.5	2270@50	-	41
TXR33	33X12.50R15LT	108Q	C	20	OWL	10.0	12.4	32.6	2205@35	-	53

WILD COUNTRY RADIAL RVT

PREMIUM MUD TERRAIN

LARGE OPEN SELF-CLEANING TREAD DESIGN PROVIDES SUPERIOR OFF-ROAD TRACTION.

- *Deep Aggressive Tread Design Provides Superior Off-Road Performance*
- *Self Cleaning Tread Pattern Maintains Excellent Traction*
- *Staggered Tread Elements For A Quieter Smoother Ride*
- *Stylized Outline White Letters*
- *Pinned For Studs*



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	MAX. LOAD LBS.@ PSI		SHIP WEIGHT (lbs.)
									SINGLE	DUAL	
FW-12	LT235/75R15	104/101Q	C	18	OWL	6.5	9.0	28.9	1985@50	1820@50	33
FW-17	LT235/85R16	120/116N	E	18	OWL	6.5	9.4	29.0	3042@80	2778@80	45
PE-17*	LT235/85R16	120/116N	E	18	OWL	6.5	9.3	31.8	3042@80	2778@80	44
FW-85	LT255/85R16	119/116N	D	17	OWL	7.0	9.4	29.0	3000@65	2755@65	45
FW-38	LT245/75R16	120/116N	E	17	OWL	7.0	9.5	30.7	3042@80	2778@80	43
FW-32	LT265/75R16	112/109N	C	18	OWL	7.5	9.4	29.0	2470@50	2270@50	45
FW-39	LT265/75R16	123/120N	E	18	OWL	7.5	10.1	32.0	3415@80	3085@80	49
FW-88	LT285/75R16	122/119N	D	18	OWL	8.0	9.4	29.0	3305@65	3000@65	54
FW-77	LT315/75R16	121N	D	20	OWL	8.5	12.5	34.8	3195@50	-	64
FW-78	30X9.50R15LT	104Q	C	19	OWL	7.5	9.4	29.0	1985@50	-	37
FW-46	31X10.50R15LT	109Q	C	20	OWL	8.5	10.5	30.5	2270@50	-	41
FW-41	32X11.50R15LT	113Q	C	20	OWL	9.0	9.4	29.0	2535@50	-	45
FW-33	33X12.50R15LT	108Q	C	20	OWL	10.0	12.8	32.5	2205@35	-	52
FW-76	35X12.50R15LT	113Q	C	20	OWL	10.0	9.4	29.0	2535@35	-	64
FW-68	33X12.50R16.5LT	118N	D	20	OWL	9.8	12.7	32.5	2910@50	-	57
FW-93	33X12.50R17LT	114Q	D	20	OWL	10.0	9.4	29.0	2600@50	-	57
FW-94	35X12.50R17LT	119Q	D	20	OWL	10.0	12.7	34.9	3000@50	-	63

* Same Tread Design - Branded Power King Radial RVT (See picture on page 31)

ARCTIC CLAW WINTER TIRE

WINTER TIRES - PASSENGER

A PREMIUM STUDDABLE WINTER TIRE. DESIGNED TO COMBINE MAXIMUM TRACTION IN WET, SLUSH, AND SNOW WITH A SMOOTH AND QUIET RIDE. WINTER PERFORMANCE PACKAGED WITH AN ATTRACTIVE HIGHLY STYLIZED SIDEWALL.

- *High Traction Tread Design Balances Wet And Dry Performance With A Quiet Ride*
- *Deep Lateral And Notched Circumferential Grooves Maximize Water And Snow Evacuation*
- *Patented "Snow Groove" Provides Superior Snow And Ice Traction*
- *Studdable Winter Tire For Superior Ice Traction*
- *Enhanced Stud Retention*



Meets the Severe Snow Requirement of the Rubber Manufacturers Association (RMA)



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	STUD SIZE (TSM#)	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
ACT06	155/80R13	79S	SL	13	WW	4.5	6.1	23.0	12	963 @ 44	14
ACT16	175/70R13	82S	SL	13	BLK	5.0	6.8	22.9	12	1047 @ 44	15
ACT38	185/75R14	89S	SL	13	WW	5.0	7.2	25.1	12	1279 @ 44	18
ACT39	195/75R14	92S	SL	13	WW	5.5	7.6	25.7	12	1389 @ 44	19
ACT47	205/75R14	95S	SL	14	WW	5.5	8.0	26.2	13	1521 @ 44	21
ACT21	175/70R14	84S	SL	13	BLK	5.0	6.8	23.9	13	1102 @ 35	17
ACT24	185/70R14	88S	SL	13	BLK	5.5	7.5	24.5	12	1235 @ 44	18
ACT25	195/70R14	91S	SL	13	BLK	6.0	7.8	25.0	12	1356 @ 44	18
1330069*	205/70R14	95S	SL	13	WW	6.0	8.1	25.4	12	1521 @ 35	20
ACT46	215/70R14	96S	SL	13	WW	6.5	8.5	25.9	12	1565 @ 44	22
ACT61	175/65R14	82T	SL	13	BLK	5.0	6.9	23.1	12	1047 @ 44	16
ACT62	185/65R14	86T	SL	13	BLK	5.5	7.4	23.6	12	1168 @ 44	17
ACT35	195/60R14	86T	SL	13	BLK	6.0	7.8	23.3	12	1168 @ 44	19
ACT34	205/75R15	97S	SL	14	WW	5.5	8.0	27.2	13	1609 @ 44	22
ACT45	215/75R15	100S	SL	14	WW	6.0	8.4	27.8	13	1764 @ 44	24
ACT49	225/75R15	102S	SL	14	WW	6.0	8.7	28.3	13	1874 @ 44	26
ACT64	235/75R15	105S	SL	14	WW	6.5	9.1	28.9	13	2039 @ 44	27
ACT29	205/70R15	96S	SL	13	WW	6.0	8.0	26.4	12	1565 @ 44	21
ACT33	215/70R15	98S	SL	13	WW	6.5	8.4	26.9	12	1653 @ 44	23
ACT40	225/70R15	100S	SL	13	WW	6.5	8.7	27.4	12	1764 @ 44	25
ACT27	185/65R15	88T	SL	13	BLK	5.5	7.6	24.5	12	1235 @ 44	19
ACT28	195/65R15	91T	SL	13	BLK	6.0	7.9	25.0	12	1356 @ 44	20
ACT67	205/65R15	94T	SL	13	BLK	6.0	8.0	25.5	12	1477 @ 44	22
ACT68	215/65R15	96T	SL	13	BLK	6.5	8.6	26.0	12	1565 @ 44	24
ACT73	185/60R15	84T	SL	13	BLK	5.5	7.4	23.9	12	1102 @ 44	19

* Tread Design And Brand Vary

ARCTIC CLAW WINTER TX1

WINTER TIRES - PASSENGER

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	STUD SIZE (TSM#)	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
ACT41	195/60R15	88T	SL	13	BLK	6.0	7.8	24.3	12	1235 @ 44	21
ACT43	205/60R15	91T	SL	13	BLK	6.0	8.2	24.8	12	1356 @ 44	22
ACT44	215/60R15	94T	SL	13	BLK	6.5	8.6	25.2	12	1477 @ 44	23
ACT53	195/55R15	85T	SL	13	BLK	6.0	7.9	23.8	12	1135 @ 44	20
ACT55	215/65R16	98T	SL	13	BLK	6.5	8.6	27.0	12	1653 @ 44	26
ACT99	235/65R16	103T	SL	13	BLK	7.0	9.6	27.9	12	1929 @ 44	27
ACT51	205/60R16	92T	SL	13	BLK	6.0	8.3	25.8	12	1389 @ 44	23
ACT48	215/60R16	95T	SL	13	BLK	6.5	8.5	26.2	12	1521 @ 44	24
ACT52	225/60R16	98T	SL	13	BLK	6.5	8.8	26.6	12	1653 @ 44	25
ACT56	235/60R16	100T	SL	13	BLK	7.0	9.5	27.0	12	1764 @ 44	28
ACT42	205/55R16	91T	SL	12	BLK	6.5	8.4	24.8	12	1356 @ 44	23
ACT57	215/55R16	97T	XL	13	BLK	7.0	8.9	25.4	12	1609 @ 50	24
ACT37	205/50R16	87T	SL	13	BLK	6.5	8.3	24.3	12	1201 @ 44	21
ACT97	215/65R17	99T	SL	13	BLK	6.5	8.9	28.1	12	1709 @ 44	26
ACT95	215/60R17	96T	SL	13	BLK	6.5	8.9	27.2	12	1565 @ 44	25
ACT72	225/60R17	99T	SL	13	BLK	6.5	9.1	27.7	12	1709 @ 44	28
ACT71	215/55R17	94T	SL	13	BLK	7.0	8.9	26.4	12	1477 @ 44	25
ACT88	225/55R17	97T	SL	13	BLK	7.0	9.2	26.9	12	1609 @ 44	28
ACT89	235/55R17	99T	SL	13	BLK	7.5	8.9	27.2	12	1709 @ 44	30
ACT58	215/50R17	91T	SL	13	BLK	7.0	8.8	25.7	12	1356 @ 44	25
ACT7C	225/45R17	94T	XL	13	BLK	7.5	8.9	25.1	12	1477 @ 50	24
ACT54	235/45R17	94T	SL	13	BLK	8.0	8.9	25.5	12	1477 @ 44	25



Meets the Severe Snow Requirement of the Rubber Manufacturers Association (RMA)

ARCTIC CLAW WINTER Xs1

WINTER TIRES - SUV/LIGHT TRUCK

A PREMIUM STUDDABLE WINTER TIRE. DESIGNED FOR CROSSOVERS, SUV'S AND LIGHT TRUCKS TO COMBINE MAXIMUM TRACTION IN WET, SLUSH, AND SNOW WITH A SMOOTH AND QUIET RIDE. WINTER PERFORMANCE PACKAGED WITH AN ATTRACTIVE HIGHLY STYLIZED SIDEWALL.

- High Traction Tread Design Balances Wet And Dry Performance With A Quiet Ride
- "D-square" sipe technology for enhanced wet and winter weather performance
- Patented "Snow Groove" Provides Superior Snow And Ice Traction
- Studdable Winter Tire For Superior Ice Traction
- Enhanced Stud Retention



Meets the Severe Snow Requirement of the Rubber Manufacturers Association (RMA)



ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	STUD SIZE (TSM#)	SINGLE MAX. LOAD LBS. @ PSI	SHIP WEIGHT (lbs.)
1340044*	235/70R15	103S	SL	15	BLK	7.0	9.7	28.0	13	1929@35	30
ACX76	225/75R16	104S	SL	15	BLK	6.0	8.7	29.2	13	1984@44	31
1340024*	235/75R16	108S	SL	15	BLK	6.5	9.3	29.9	13	2205@35	35
ACX79	245/75R16	111S	SL	15	BLK	7.0	9.6	30.4	13	2403@44	35
ACX81	265/75R16	116S	SL	15	BLK	7.5	10.6	31.6	13	2756@44	39
ACX75	215/70R16	100S	SL	15	BLK	6.5	8.8	27.8	13	1764@44	29
ACX77	225/70R16	103S	SL	15	BLK	6.5	9.0	28.3	13	1929@44	30
ACX53	235/70R16	106S	SL	15	BLK	7.0	9.4	28.9	13	2094@44	32
ACX80	245/70R16	107S	SL	15	BLK	7.0	9.9	29.5	13	2149@44	34
ACX86	255/70R16	111S	SL	15	BLK	7.5	10.3	29.9	13	2403@44	35
ACX93	265/70R16	112S	SL	15	BLK	8.0	10.8	30.4	13	2469@44	39
ACX89	245/70R17	110S	SL	15	BLK	7.0	9.9	30.5	0	2337@44	35
ACX87	265/70R17	115S	SL	15	BLK	8.0	10.7	31.4	13	2679@44	40
ACX78	235/65R17	104S	SL	14	OWL	7.0	9.5	29.1	13	1984@44	33
ACX54	245/65R17	107S	SL	14	OWL	7.0	9.8	29.5	13	2149@44	35

* Tread Design And Brand Vary

• NOTE: LT Sizes Continued On Next Page

ARCTIC CLAW WINTER X61

WINTER TIRES - SUV/LIGHT TRUCK

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	TREAD DEPTH (32nd)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAM.	STUD SIZE (TSM#)	MAX. LOAD LBS.@ PSI		SHIP WEIGHT (lbs.)
										SINGLE	DUAL	
ACX12	LT235/75R15	104/101Q	C	17	BLK	6.5	9.0	28.8	15	1985@50	1820@50	34
ACX15	LT215/85R16	115/112Q	E	17	BLK	6.0	9.1	30.3	15	2680@80	2470@80	38
ACX17	LT235/85R16	120/116Q	E	17	BLK	6.5	9.3	31.8	15	3042@80	2778@80	42
ACX26	LT225/75R16	115/112Q	E	17	BLK	6.0	9.0	29.3	15	2680@80	2470@80	40
ACX38	LT245/75R16	120/116Q	E	17	BLK	7.0	9.6	30.4	15	3042@80	2778@80	44
ACX39	LT265/75R16	123/120Q	E	17	BLK	7.5	10.5	31.5	15	3415@80	3085@80	49
1255040*	LT235/80R17	120/117Q	E	17	BLK	6.5	9.4	31.9	15	3085@80	2835@80	44
ACX70	LT245/70R17	119/116Q	E	17	BLK	7.0	10.1	30.5	15	3000@80	2755@80	49
ACX90	LT265/70R17	121/118Q	E	18	BLK	8.0	11.0	31.7	15	3195@80	2910@80	50
1255025*	LT275/70R17	114/110Q	C	18	BLK	8.0	11.3	32.2	15	2600@50	2335@50	47
ACX41	31X10.50R15LT	109Q	C	19	BLK	8.5	10.5	30.3	15	2270@50	-	40

* Tread Design And Brand Vary



Meets the Severe Snow Requirement of the Rubber Manufacturers Association (RMA)

NEUTRAL TIRE PICTURES

PASSENGER TIRES



**GRAND PRIX
PERFORMANCE GT
(39B, 67B)**



**GRAND SPIRIT
RADIAL G/T
(J2-46)**



**GRAND SPIRIT
TOURING SLi
(SLG)**



**GRAND SPIRIT
TOURING
(AY)**



**CLASSIC RADIAL
(Q4, V2)**



**RADIAL XL
(F2-60)**

NEUTRAL TIRE PICTURES

SUV / LIGHT TRUCK TIRES



**WILD SPIRIT
SPORT H/T
(WSH)**



**WILD SPIRIT
RADIAL A/T
(FJ)**



**WILD SPIRIT
RADIAL AT/S
(WST)**



**POWER KING
RADIAL A/S
(ET)**



**WILD SPIRIT
RADIAL A/S
(U5)**



**TRIANGLE
TR656
(GX-61)**



**POWER KING
RADIAL RVT
(PE)**

NATIONWIDE LIMITED WARRANTY

WORKMANSHIP AND MATERIAL

Your new tire, bearing our Multi-Mile® trademark or other brand tires marketed by TBC CORPORATION (TBC), is warranted against defects in workmanship or materials. The extent of this protection is based on the kind of vehicle or equipment you use and the records you keep. When you present a claim for an unserviceable tire, you must be able to identify yourself as the purchaser of that tire. You must also show that the tire has only been used on the vehicle on which it was originally installed. To prevent disappointment, keep all papers given to you by the Multi-Mile® dealer when you purchase the tire.

ELIGIBILITY:

You are eligible for the benefits of this warranty if you are the original owner of a tire and the tire remains on the vehicle it was originally installed. Providing the tire has a TBC Corporation trademark and has manufacturer's serial number indicating TBC as the brand owner.

COVERAGE:

If any tire covered by this policy becomes unserviceable during its original tread life because of a defect in workmanship and/or materials, the servicing authorized TBC Corporation Dealer will make a prorata allowance toward the purchase of a comparable new Multi-Mile® or comparable TBC brand tire, the consumer will be responsible for mounting and balancing. If the tire becomes unserviceable because of a defect in workmanship and/or materials during the free replacement period, first 2/32nds for radial or the first 1/32nd for bias ply tires the tire will be replaced free of charge including mounting and balancing.

Tread life and treadwear are measured by the depth of the remaining tread on a tire. A tire has delivered its full original tread life when worn down to the last 2/32" of tread. Treadwear safety indicators (where applicable) molded into the tire will appear on the tire, when that point of wear is reached which indicates that the tires must be replaced. Failure to replace tires may result in loss of vehicle control and serious injury.

LIMITATIONS:

This warranty is applicable only in the United States. Not covered are:

- Tires branded "NA" (not adjustable) in the vicinity of the serial number are sold "AS IS" without warranty.
- Tires branded "BLEM" for appearance imperfections only.
- Automobile tires used in commercial applications;
- Ozone and weather checking over four years from the date of manufacture;
- Personal injury or property damage, including injury and damage arising from failure to observe the safety information on the reverse side thereof;
- Tire failure or loss due to improper mounting procedures (including broken beads), improper inflation, overloading, running flat, chain damage, mechanical condition of the vehicle, fire, theft, vandalism, highway conditions, road hazard

damage, wreck or collision, tire neglect or mistreatment, tire conditions resulting from intentional tire alterations such as the addition of white inlay, or balancing or sealing materials, or other conditions beyond TBC's control;

- LOSS OF TIME, INCONVENIENCE, LOSS OF USE OF THE VEHICLE, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages so such limitations or exclusions may not apply to you.

NO EXPRESS WARRANTY IS GIVEN OTHER THAN THAT STATED HEREIN. NO IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHERWISE IS GIVEN ON AUTOMOBILE TIRES USED IN COMMERCIAL APPLICATIONS, TIRES SOLD AS IS, AND TIRES NOT NORMALLY USED FOR PERSONAL, FAMILY OR HOUSEHOLD PURPOSES.

OWNERS OBLIGATIONS:

a. If a tire which is subject to this warranty becomes unserviceable, you should take the tire back to the dealer where you bought it. Should this, for any reason, not be possible, you may take it to the nearest Multi-Mile® dealer. Please consult the telephone directory for locations. To assist you in locating the nearest Multi-Mile® dealer you may telephone toll-free DURING NORMAL BUSINESS HOURS: (800) 238-6469. It is your obligation to present the unserviceable tire to the dealer.

b. Replacement under this adjustment policy does not include taxes, dealer handling charge or any services (including mounting and balancing) ordered by you at the time of adjustment.

c. No claim will be recognized unless accompanied by proof of purchase, identification of you as original purchaser, and identification of the vehicle on which the tire was originally installed.

LEGAL RIGHTS:

This warranty gives you specific legal rights, and you may also have other rights which may vary from state to state.

TIRE REGISTRATION:

You will receive a tire registration form from your tire dealer at the time you purchase your tires. You are encouraged to complete this form and submit it to the tire manufacturer or brand name owner named on the registration card. This will enable the tire manufacturer or brand name owner to contact you directly in the event your tires are recalled for safety reasons.

Toll-Free Telephone Number:

1-800-238-6469

Visit Our Web-Site:

www.multimiletires.com



MULTI-MILE is the registered trademark of TBC Corporation
Distributed by TBC PRIVATE BRANDS
MEMPHIS, TENNESSEE 38141

Visit Our Website: www.multimiletires.com



MMPB-309

Multi-Mile[®]

MAXIMUM MILEAGE SECURITY AND COMFORT